

SINGLE PHASE
230 V / 50 Hz
DIESEL

MIXTE 5000 DXL15 YN DE
 Welders Range

MAX. OUTPUT
5.15 kW

LONG
AUTONOMY

START
ELECTRIC

CURRENT 
AC WELDING

ELECTROD DIAM.
5 mm

ELECTROD
RUTILE



powered by
YANMAR

At the same time generator and welder, with AC welding current. In welder position, you can make welding with alternating welding current.

Standard Equipment

- ✓ 4-stroke Diesel engine
- ✓ Electric start + Battery
- ✓ Low oil pressure security
- ✓ 2 Single phase sockets 10/16 A Schuko
- ✓ Sockets protected by thermal circuit breaker
- ✓ Intensity rheostat
- ✓ Electric source selector
- ✓ Welding terminals
- ✓ Heavy duty steel frame

Optional Equipment

- + Wheelbarrow kit N/360 AXE
- + Welding kit: CABLE KIT N° 1
- + Kit interdif (factory option): Earth leakage circuit breaker 30 mA + Steel Ground Rod + box



MIXTE 5000 DXL15 YN DE

Type		1 phase
Voltage regulator		Capacitor
Maximum output	kW	5.15
Continuous operating power (COP)	kW	4.5
Maximum Amps	A	22.3
AC voltage	V	230
Frequency	Hz	50
Noise power level CEE (LwA)	dB(A)	103
Noise power level @ 7 m	dB(A)	78
Maximum electrode diameter	mm	Ø 4
Welding Amp Range	A	60 → 180
Striking Alternative Current	V	50 - 62.5
Minimum welding voltage	V	22.4
Duty cycle (35%)	A	180
Engine model		YANMAR L100
Maximum output	HP	9.3
Fuel type		Diesel (Do not use domestic or heating oil)
Fuel tank capacity	L	15
Autonomy (¾ of the continuous output)	h	9 h 45
Dimensions L x l x H	mm	875 x 535 x 635
Packaging dimensions L x W x H	mm	895 x 555 x 655
Net Weight	kg	109
Gross weight	kg	111



Equipment intended to be installed with all the proper rules, inside a building or reserved for use in a country not subject to Directive 2000/14/EC (excluding UE and affiliated countries).